

3. CIF DATA DEFINITION AND CLASSIFICATION

_wave_vector_seq_id* is a pointer to the description of the separate modulation wave vectors and must match one of the identifiers *_atom_site_Fourier_wave_vector_seq_id* listed separately in the *ATOM_SITE_FOURIER_WAVE_VECTOR* category. Likewise, the **_atom_site_label* data item must match a value of *_atom_site_label* in the main list of atom positions. This is how the modulation is linked to the atom list. The item *_atom_site_displace_Fourier_id* is the formal key for the *ATOM_SITE_DISPLACE_FOURIER* category. It is used to locate the matching Fourier coefficients in the *ATOM_SITE_DISPLACE_FOURIER_PARAM* category. The coefficients may be reported in a sine–cosine (*_atom_site_displace_Fourier_param_sin*, **_cos*) or modulus–argument (_mod*, **_phase*) representation.

Where a group of atoms is treated as a rigid group, the categories above describe only the translational part of the positional distortion. *ATOM_SITE_ROT_FOURIER* and *ATOM_SITE_ROT_FOURIER_PARAM* are used to describe the rotational components.

ATOM_SITE_OCC_FOURIER and *ATOM_SITE_U_FOURIER*, and their associated **_PARAM* categories, are the analogous categories for the modulation of site occupation and thermal parameters.

All the categories above describe the properties of individual atom sites. Larger-scale descriptions of the displacive modulation or of the rotational component of a rigid group are covered by the categories *ATOM_SITES_DISPLACE_FOURIER* and *ATOM_SITES_ROT_FOURIER*, each of which at present contains one descriptive data item.

The *ATOM_SITES_MODULATION* category contains data items describing the initial phases of the modulation waves, which are essential for determining the space group of the commensurate superstructure. More details are given in the dictionary.

3.4.3.3.3. Special modulation functions

Data items in these categories are as follows:

- (a) *ATOM_SITE_DISPLACE_SPECIAL_FUNC*
- *_atom_site_displace_special_func_atom_site_label*
→ *_atom_site_label*
_atom_site_displace_special_func_sawtooth_ax
_atom_site_displace_special_func_sawtooth_ay
_atom_site_displace_special_func_sawtooth_az
_atom_site_displace_special_func_sawtooth_c
_atom_site_displace_special_func_sawtooth_w
- (b) *ATOM_SITE_OCC_SPECIAL_FUNC*
- *_atom_site_occ_special_func_atom_site_label*
→ *_atom_site_label*
_atom_site_occ_special_func_crenel_c
_atom_site_occ_special_func_crenel_w

The bullet (•) indicates a category key. The arrow (→) is a reference to a parent data item.

Several data items cover modulation functions that are not expressed as Fourier expansions. The examples in the current msCIF dictionary are restricted to the one-dimensional modulations (sawtooth displacive and occupational crenel functions) implemented in the program *JANA2000* (see Section 3.4.2).

3.4.3.3.4. Molecular or packing geometry

New data items in these categories are as follows:

- (a) *GEOM_ANGLE*
- _geom_angle_av*
 - _geom_angle_max*
 - _geom_angle_min*
 - _geom_angle_site_ssg_symmetry_1*
 - _geom_angle_site_ssg_symmetry_2*
 - _geom_angle_site_ssg_symmetry_3*

- (b) *GEOM_BOND*
- _geom_bond_distance_av*
 - _geom_bond_distance_max*
 - _geom_bond_distance_min*
 - _geom_bond_site_ssg_symmetry_1*
 - _geom_bond_site_ssg_symmetry_2*

- (c) *GEOM_CONTACT*
- _geom_contact_distance_av*
 - _geom_contact_distance_max*
 - _geom_contact_distance_min*
 - _geom_contact_site_ssg_symmetry_1*
 - _geom_contact_site_ssg_symmetry_2*

- (d) *GEOM_TORSION*
- _geom_torsion_av*
 - _geom_torsion_max*
 - _geom_torsion_min*
 - _geom_torsion_site_ssg_symmetry_1*
 - _geom_torsion_site_ssg_symmetry_2*
 - _geom_torsion_site_ssg_symmetry_3*
 - _geom_torsion_site_ssg_symmetry_4*

For each of the geometry categories, there are two groups of extensions. One set covers maximum, minimum and average values of bonds, contact distances, angles and torsion angles. The other extends the symmetry-operation code used in geometry listings in the core CIF dictionary (see Section 3.2.4.3.2) to the higher-dimensional superspace form.

3.4.3.3.5. Symmetry information

New data items in these categories are as follows:

- (a) *SPACE_GROUP*
- _space_group_ssg_IT_number*
 - _space_group_ssg_name*
 - _space_group_ssg_name_IT*
 - _space_group_ssg_name_WJJ*
 - _space_group_ssg_WJJ_code*
- (b) *SPACE_GROUP_SYMOP*
- _space_group_symop_ssg_id*
 - _space_group_symop_ssg_operation_algebraic*

At present, the msCIF dictionary extends the core CIF dictionary symmetry categories to describe superspace groups for one-dimensional modulated structures in four ways: as the superspace-group number in Janssen *et al.* (2004) (*_space_group_ssg_IT_number*), as the *International Tables* superspace-group symbol (**_ssg_name_IT*), as one of the notations from de Wolff *et al.* (1981) (**_ssg_name_WJJ*, **_ssg_WJJ_code*), or in some other formalism (**_ssg_name*). At present, superspace-group names for higher dimensions can only be indicated using *_space_group_ssg_name*.

Symmetry operations in the superspace group are specified in the *SPACE_GROUP_SYMOP* category by an obvious extension to the method used in the core dictionary. These items must always be present in a CIF corresponding to a modulated or composite structure.

3.4.3.4. File metadata

The categories modified in the msCIF dictionary to formalize the construction of a multi-block description of modulated or composite structures are as follows:

- AUDIT group
- AUDIT ¶
- AUDIT_LINK ¶

Categories marked with ¶ are already defined in the core CIF dictionary.